

华为坤灵SOHO网络融合网关全家福

NetEngine 系列融合网关



AR303

- 1*GE Combo ; 4*GE
- 转发性能(64字节): 1Mpps
- 带机量: 200
- 最大功耗: 24W



AR303W

- 1*GE Combo ; 4*GE
- 转发性能(64字节): 1Mpps
- 带机量: 200
- 最大功耗: 24W
- Wi-Fi: 802.11b/g/n, 2.4GHz, 2 x 2 MIMO ; 802.11ac, 5GHz, 2 x 2 MIMO



AR720


- 2*GE Combo; 8*GE
- 转发性能(64字节): 9Mpps~25Mpps
- 带机量: 700
- 最大功耗: 20W



AR730

- 1*10GE光, 2*GE Combo; 1*GE Combo, 8*GE
- 转发性能(64字节): 9Mpps~25Mpps
- 带机量: 1200
- 最大功耗: 20W

eKitEngine S380系列路由交换一体机




S380-L4T1T

- 4*GE电; 1*GE电
- 带机量: 200
- 交换容量: 8Gbps
- 出口带宽: 1Gbps
- 管理AP数: 32



S380-L4P1T

- 4*GE电; 1*GE电
- 带机量: 200
- PoE功率: 50W
- 交换容量: 8Gbps
- 出口带宽: 1Gbps
- 管理AP数: 32



S380-S8T2T

- 8*GE电; 2*GE电
- 带机量: 300
- 交换容量: 16Gbps
- 出口带宽: 2Gbps
- 管理AP数: 64



S380-S8P2T

- 8*GE电; 2*GE电
- 带机量: 300
- PoE功率: 124W
- 交换容量: 16Gbps
- 出口带宽: 2Gbps
- 管理AP数: 64



S380-H8T3ST

- 8*GE电; 2*GE电; 1*GE光
- 带机量: 500
- 交换容量: 16Gbps
- 出口带宽: 2Gbps
- 管理AP数: 128

华为坤灵SOHO网络交换机全家福

FutureMatrix S110系列无管理交换机


S110-5T


- 5*GE电
- 交换容量: 10Gbps
- 包转发率: 7.44Mpps


S110-8T

- 8*GE电
- 交换容量: 16Gbps
- 包转发率: 11.9Mpps


S110-8LP2ST

- 8*GE电; 1*GE光, 1*GE电
- PoE功率: 54W
- 交换容量: 20Gbps
- 包转发率: 14.88Mpps


S110-8P1T

- 8*GE电; 1*GE电
- PoE功率: 124W
- 交换容量: 18Gbps
- 包转发率: 13.39Mpps


S110-8P2ST

- 8*GE电; 1*GE光, 1*GE电
- PoE功率: 124W
- 交换容量: 20Gbps
- 包转发率: 14.88Mpps


S110-8T2ST

- 8*GE电; 1*GE光, 1*GE电
- 交换容量: 20Gbps
- 包转发率: 14.88Mpps


S110-4P1T-BU

- 4*GE电; 1*GE电
- PoE功率: 54W
- 交换容量: 10Gbps
- 包转发率: 7.44Mpps


S110-8LP2T-BU

- 8*GE电; 2*GE电
- PoE功率: 50W
- 交换容量: 20Gbps
- 包转发率: 14.88Mpps


S110-8P2T-BU


- 8*GE电; 2*GE电
- PoE功率: 124W
- 交换容量: 20Gbps
- 包转发率: 14.88Mpps


S110-16T

- 16*GE电
- 交换容量: 32Gbps
- 包转发率: 23.81Mpps


S110-16T2S

- 16*GE电; 2*GE光
- 交换容量: 36Gbps
- 包转发率: 26.79Mpps


S110-16P2SR

- 16*GE电; 2*GE光
- PoE功率: 247W
- 交换容量: 36Gbps
- 包转发率: 26.78Mpps


S110-24TR

- 24*GE电
- 交换容量: 48Gbps
- 包转发率: 35.71Mpps


S110-24T2S

- 24*GE电; 2*GE光
- 交换容量: 52Gbps
- 包转发率: 38.69Mpps


S110-24T2SR

- 24*GE电; 2*GE光
- 交换容量: 52Gbps
- 包转发率: 38.69Mpps


S110-24FP2SR

- 22*FE电, 2*GE电; 2*GE光
- PoE功率: 370W
- 交换容量: 12.4Gbps
- 包转发率: 9.23Mpps


S110-24LP2SR

- 24GE电; 2*GE光
- PoE功率: 247W
- 交换容量: 52Gbps
- 包转发率: 38.69Mpps


S110-24P2SR

- 24GE电; 2*GE光
- PoE功率: 370W
- 交换容量: 52Gbps
- 包转发率: 38.69Mpps

FutureMatrix S210系列WEB管理交换机


S210-8T

- 8*GE电
- 交换容量: 56Gbps
- 包转发率: 12Mpps


S210-8T2ST

- 8*GE电; 1*GE光, 1*GE电
- 交换容量: 192Gbps
- 包转发率: 15Mpps


S210-8P1T

- 8*GE电; 1*GE电
- PoE功率: 124W
- 交换容量: 56Gbps
- 包转发率: 13.5Mpps


S210-8P2ST

- 8*GE电; 1*GE光, 1*GE电
- PoE功率: 124W
- 交换容量: 192Gbps
- 包转发率: 15Mpps


S210-24T2SR

- 24*GE电; 2*GE光
- 交换容量: 192Gbps
- 包转发率: 39Mpps


S210-24T4SR

- 24*GE电; 4*GE光
- 交换容量: 336Gbps
- 包转发率: 42Mpps


S210-24P2SR

- 24*GE电; 2*GE光
- PoE功率: 370W
- 交换容量: 192Gbps
- 包转发率: 39Mpps


S210-24P4SR

- 24*GE电; 4*GE光
- PoE功率: 370W
- 交换容量: 336Gbps
- 包转发率: 42Mpps

华为坤灵SOHO网络交换机全家福

eKitEngine S220系列全管理交换机



S220-24T4X

- 24*GE电,4*10GE光
- 交换容量: 336Gbps
- 包转发率: 108Mpps



S220-24P4X

- 24*GE电,4*10GE光
- PoE功率: 400W
- 交换容量: 336Gbps
- 包转发率: 108Mpps



S220-48T4S

- 48*GE电,4*GE光
- 交换容量: 432Gbps
- 包转发率: 108Mpps



S220-48P4S

- 48*GE电,4*GE光
- PoE功率: 380W
- 交换容量: 432Gbps
- 包转发率: 108Mpps



S220-48T4X

- 48*GE电,4*10GE光
- 交换容量: 432Gbps
- 包转发率: 144Mpps



S220-48P4X

- 48*GE电,4*10GE光
- PoE功率: 380W
- 交换容量: 432Gbps
- 包转发率: 144Mpps

FutureMatrix S200系列全管理交换机



S200-8T4S/-QA2

- 8*GE电; 4*GE光
- 交换容量: 336Gbps/1.008Tbps
- 包转发率: 18Mpps~54Mpps



S200-8P4S/-QA2

- 8*GE电; 4*GE光
- PoE功率: 124W
- 交换容量: 336Gbps/1.008Tbps
- 包转发率: 18Mpps ~54Mpps



S200-24T4X-QA2

- 24*GE电; 4*10GE光
- 交换容量: 336Gbps/1.008Tbps
- 包转发率: 96Mpps ~288Mpps



S200-24P4X-A2

- 24*GE电; 4*10GE光
- PoE功率: 400W
- 交换容量: 336Gbps/1.008Tbps
- 包转发率: 96Mpps ~288Mpps



S200-24T4S/-QA2

- 24*GE电; 4*GE光
- 交换容量: 336Gbps/1.008Tbps
- 包转发率: 42Mpps ~126Mpps




S200-24P4S/-A2

- 24*GE电; 4*GE光
- PoE功率: 400W
- 交换容量: 336Gbps/1.008Tbps
- 包转发率: 42Mpps ~126Mpps



S200-32ST4X

- 24*GE光, 8*GE电; 4*10GE光
- 交换容量: 432Gbps
- 包转发率: 108Mpps



S200-48T4X

- 48*GE电; 4*10GE光
- 交换容量: 432Gbps
- 包转发率: 132Mpps



S200-48P4X

- 48*GE电; 4*10GE光
- PoE功率: 380W
- 交换容量: 432Gbps
- 包转发率: 132Mpps



S200-48T4S

- 48*GE电; 4*GE光
- 交换容量: 432Gbps
- 包转发率: 78Mpps

华为坤灵SOHO网络交换机全家福

FutureMatrix S300系列全管理交换机



S300-8T4S/-QA2

- 8*GE电; 4*GE光
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 27Mpps/102Mpps



S300-8P4S/-QA2

- 8*GE电; 4*GE光
- PoE功率: 124W
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 27Mpps/102Mpps



S300-16T4S

- 16*GE电; 4*GE光
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 39Mpps/114Mpps



S300-16P4S

- 16*GE电; 4*GE光
- PoE功率: 380W
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 39Mpps/102Mpps



S300-24T4S/-QA2

- 24*GE电; 4*GE光
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 51Mpps/126Mpps



S300-24P4S/-A2

- 24*GE电; 4*GE光
- PoE功率: 380W
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 51Mpps/126Mpps



S300-48T4S

- 48*GE电; 4*GE光
- 交换容量: 432Gbps/4.32Tbps
- 包转发率: 87Mpps/166Mpps

华为坤灵SOHO网络交换机全家福

eKitEngine S310系列全管理交换机



S310-24T4X

- 24*GE电,4*10GE光
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 108Mpps/126Mpps



S310-24P4X

- 24*GE电,4*10GE光
- PoE功率: 400W
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 108Mpps/126Mpps



S310-48T4S

- 48*GE电,4*GE光
- 交换容量: 432Gbps/4.32Tbps
- 包转发率: 108Mpps/166Mpps



S310-48P4S

- 48*GE电,4*GE光
- PoE功率: 380W
- 交换容量: 432Gbps/4.32Tbps
- 包转发率: 108Mpps/166Mpps




S310-48T4X

- 48*GE电,4*10GE光
- 交换容量: 758Gbps/7.58Tbps
- 包转发率: 148Mpps/222Mpps



S310-48P4X

- 48*GE电,4*10GE光
- PoE功率: 380W
- 交换容量: 758Gbps/7.58Tbps
- 包转发率: 148Mpps/222Mpps



S310-24PN4X

- 24*2.5GE电,4*10GE光
- PoE功率: 400W
- 交换容量: 598Gbps/5.98Tbps
- 包转发率: 148Mpps/222Mpps



S310-24ST4X

- 24*GE光(8个复用GE Combo), 4*10GE光
- 交换容量: 598Gbps/5.98Tbps
- 包转发率: 148Mpps/222Mpps

华为坤灵SOHO网络交换机全家福

FutureMatrix S500/S600系列全管理交换机



S500-8T4S

- 8*GE电; 4*GE光
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 72Mpps/102Mpps



S500-8P4S

- 8*GE电; 4*GE光
- PoE功率: 124W
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 27Mpps/102Mpps



S500-16T4S

- 16*GE电; 4*GE光
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 72Mpps/102Mpps



S500-16P4S

- 16*GE电; 4*GE光
- PoE功率: 380W
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 84Mpps/114Mpps



S500-24T4S

- 24*GE电; 4*GE光
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 96Mpps/126Mpps



S500-24P4S

- 24*GE电; 4*GE光
- PoE功率: 380W
- 交换容量: 336Gbps/3.36Tbps
- 包转发率: 96Mpps/126Mpps



S500-32ST4X

- 24*GE光, 8*GE电; 4*10GE光
- 交换容量: 432Gbps/4.32Tbps
- 包转发率: 120Mpps/138Mpps



S500-48T4S

- 48*GE电; 4*GE光
- 交换容量: 432Gbps/4.32Tbps
- 包转发率: 132Mpps/162Mpps



S600-S24S28X

- 24*GE光; 28*10GE光
- 交换容量: 2.56Tbps/23.04Tbps
- 包转发率: 456Mpps

eKitEngine S530 系列全管理交换机



S530-24T4XE

- 24*GE电; 4*10GE光; 2个专用堆叠口
- 交换容量: 672Gbps/6.72Tbps
- 包转发率: 171Mpps



S530-24ST4XE

- 24*GE光 (8个复用GE Combo); 4*10GE光; 2个专用堆叠口
- 交换容量: 672Gbps/6.72Tbps
- 包转发率: 171Mpps



S530-48S4XE

- 48*GE光; 4*10GE光; 2个专用堆叠口
- 交换容量: 758Gbps/7.58Tbps
- 包转发率: 222Mpps

eKitEngine S7700S系列核心交换机



S7703S

- 5个总槽位, 3个业务槽位
- 双主控, 电源备份
- 整机支持 144*GE/144*10GE/24*40GE/12*100GE端口
- 交换容量38.4Tbps, 包转发率7200Mpps

华为坤灵SOHO网络 WLAN全家福

Wi-Fi 6系列面板AP



AP160

- 推荐接入用户数: 48
- 速率: 1.775Gbps
- 最大发射功率: 20dBm
- 最大功耗: 9.1W



AP161

- 推荐接入用户数: 48
- 速率: 2.975Gbps
- 最大发射功率: 20dBm
- 最大功耗: 11.6W



AP162

- 推荐接入用户数: 48
- 速率: 2.975Gbps
- 最大发射功率: 20dBm
- 最大功耗: 11.9W



AP163

- 推荐接入用户数: 64
- 速率: 2.975Gbps
- 最大发射功率: 20dBm
- 最大功耗: 11W



AP165

- 推荐接入用户数: 64
- 速率: 2.975Gbps
- 最大发射功率: 20dBm
- 最大功耗: 12W



AP263

- 推荐接入用户数: 64
- 速率: 2.975Gbps
- 最大发射功率: 23dBm
- 最大功耗: 12W



AP761

- 速率: 1.775Gbps
- 1*GE电, 1*GE光
- 最大发射功率: 28dBm
- 最大功耗: 17.7W
- 工作温度: -30°C~65°C

Wi-Fi 6系列放装AP



AP361

- 推荐接入用户数: 80
- 速率: 1.775Gbps
- 最大发射功率: 20dBm
- 最大功耗: 8.8W



AP362

- 推荐接入用户数: 80
- 速率: 2.975Gbps
- 最大发射功率: 20dBm
- 最大功耗: 11.2W



AP363

- 推荐接入用户数: 100
- 速率: 2.975Gbps
- 最大发射功率: 20dBm
- 最大功耗: 10W



AP365

- 推荐接入用户数: 120
- 速率: 2.975Gbps
- 最大发射功率: 23dBm
- 最大功耗: 11W



AP661

- 推荐接入用户数: 150
- 速率: 6.575Gbps
- 1*2.5GE电, 1*GE电
- 最大发射功率: 26dBm
- 最大功耗: 21.2W

Wi-Fi 7系列放装AP



AP371

- 推荐接入用户数: 150
- 速率: 3.57Gbps
- 最大发射功率: 23dBm
- 最大功耗: 13.6W

无线控制器



AC650-128AP

- 10*GE电, 2*10 GE光
- 转发能力: 10Gbps
- 最大可管理AP的数量: 128
- 无线用户接入能力: 1024



AC650-256AP

- 10 * GE电, 2 * 10 GE光
- 转发能力: 10Gbps
- 最大可管理AP的数量: 256
- 无线用户接入能力: 2048



AC650-512AP

- 10 * GE电, 2 * 10 GE光
- 转发能力: 12Gbps
- 最大可管理AP的数量: 512
- 无线用户接入能力: 4096


华为坤灵SOHO网络安全网关全家福

HiSecEngine 系列安全网关



UGS6106E

- 2*GE WAN; 8*GE Combo;
2*10GE SFP+
- 带机量: 100-400
- 选配冗余电源
- 赠送SSL VPN 100用户



USG6110E

- 10*GE RJ45; 2*GE SFP
- 带机量: 80
- 外置电源适配器
- 赠送SSL VPN 100用户